

**DECLARATION OF PERFORMANCE N. CPR-DE1/9050639.1**

- 1) Unique identification code of the product-type:  
**Rasco 2K FPD Vario**
- 2) Intended uses:  
**Polymer modified bitumen thick coating for waterproofing**
- 3) Manufacturer:  
**Rasco Bitumentchnik GmbH, Otto-von-Guericke-Ring 11, 65205 Wiesbaden, www.bitumentchnik.de**
- 4) Systems of AVCP:  
**System 3**  
**System 3 (for reaction to fire)**
- 5) Harmonized standards: **EN 15814:2011+A2:2014**

Notified bodies: Kiwa GmbH Flörsheim, ID-No. 1119

Notified body (for reaction to fire): Materialprüfungsamt Nordrhein-Westfalen, ID-No.0432

- 6) Performances declared:


Essential characteristics	Performances
<b>Watertightness</b> <b>Crack bridging ability</b> <b>Water resistance</b>  <b>Flexibility at low temperature</b> <b>Dimensional stability at high temperature</b> <b>Reaction to fire</b> <b>Resistance to compression</b> <b>Dangerous substances</b> <b>Durability of water tightness and reaction to fire</b>	<b>Class W2A</b> <b>Class CB2</b> <b>no coloration of the water,</b> <b>no debonding from inlay</b>  <b>no cracks</b>  <b>no sliding or draining down</b>  <b>Class E</b>  <b>Class C2A</b>  <b>NPD</b>  <b>passed</b>

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Holger Fleischmann – Plant manager**



**Augustdorf, 29.11.2022**



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the Safety Data Sheet that Rasco makes available on the website along with this current Declaration of Performance.

*DoP in Pdf format are available on the Rasco website.*

**Revision Notes:**      *first issue*

 1119	 <small>Bitumentchnik GmbH</small> <b>Otto-von-Guericke-Ring 11 - 65205 Wiesbaden</b> <b>www.bitumentchnik.de</b>
<b>22</b> <b>CPR-DE1/EN 15814:2011+A2:2014</b> <b>Rasco 2K FPD Vario</b> <i>Polymer modified bitumen thick coating for waterproofing</i>	
Watertightness Crack bridging ability Water resistance Flexibility at low temperature Dimensional stability at high temperature Reaction to fire Resistance to compression Dangerous substances Durability of water tightness and reaction to fire	Class W2A Class CB2 no coloration of the water, no debonding from inlay no cracks no sliding or draining down Class E Class C2A NPD passed

**Note:**

Rasco supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.